

Swansea University

Waste Management Guidance Note WMGN33 Waste Nano-objects, Agglomerates and Aggregates (NOAA)

Author:	Fiona Wheatley
Approved by:	Fiona Abbott
Creation date:	01/08/2019

Waste Management Guidance Note WMGN33			
Waste Nano-objects, Agglomerates and Aggregates (NOAA)			
Location Generated	CAT 2 laboratory		
EWC	Various		
Transport Class & UN Number	Various		
Туре	Hazardous		
Disposal Method	Incineration		
Bin/Bag Type	Red Bag / Yellow lidded clinical boxes		

This Waste Management Guidance Note has been developed in accordance with <u>BIS (PD</u> <u>6699-2:2007)</u>¹, PAS 138:2012², <u>UKNSG 2016</u>³ and <u>Technical Guidance WM3</u>⁴ guidance.

Duty of Care Requirements

EWC 06 Wastes from Inorganic Chemical Processes

EWC 06 07 ; wastes from Manufacture, Formulation, Supply and Use (MFSU) of halogens and halogen chemical waste

EWC 07 Wastes from Organic Chemical Process

EWC 07 01 ; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals

Description;

Nano-objects, Agglomerates and Aggregates (NOAA) are less than 100nm and greater than 1nm (PAS 138:2012) and are applicable to engineered materials that consist of nano-objects such as nanoparticles, nanofibers, nanotubes and nanowires, as well as aggregates and agglomerates of these materials.

There is currently no regulatory framework in the UK specifically for nanomaterial. Currently the manufacture of nanomaterials falls under the Control of Substances Hazardous to Health (COSHH) Regulations (2002), and the disposal of laboratory waste nanomaterial under the Waste Regulations (2011). It is a legal requirement under the Hazardous Waste Regulations to segregate hazardous wastes from non-hazardous wastes. Incorrectly disposing of hazardous waste via a non-hazardous waste stream can lead to legal and financial penalties dependent upon the severity of the noncompliance.

BIS (PD 6699-2:2007) outlines that it is a reasonable worst case assumption to consider all nanomaterial waste as potentially hazardous. This also applies to any material that has

¹ BIS Nanotechnologies – Part 2: Guide to safe handling and disposal of manufactured nanomaterials

² PAS 138:2012 Disposal of manufacturing process waste containing manufactured nano-objects. Guide

³ UK Nano Safety Group - Working Safely with Nanomaterials in Research & Development Second Edition May 2016

⁴ Guidance on the classification and assessment of waste (1st Edition v1.1) Technical Guidance WM3

come into contact with dispersible engineered NOAAs (that has not been decontaminated), which should be considered as belonging to a nanomaterial-bearing waste stream.

Waste items;

- pure NOAAs (nano-objects, agglomerates and aggregates)
- items contaminated with NOAAs, such as containers, wipes and disposable PPE
- liquid suspensions containing NOAAs
- cleaning solutions used for decontaminating
- solid matrices with NOAAs that are friable or have a nanostructure loosely attached to the surface such that they can reasonably be expected to break free or leach out when in contact with air, water, or other media when subjected to reasonably foreseeable mechanical forces.
- solid matrices with NOAAs that are non-friable

Material from hazardous or potentially hazardous nanomaterial-bearing waste streams must be disposed of as hazardous waste, and should not be put into the any other University waste stream or disposed down the drain.

NOAA can be in different forms, as produced (e.g. as a powder), or as used (e.g. embedded in a solid matrix or attached to a substrate), suspended in a gas or in a liquid; or as waste. Each of these different stages will have its own exposure pattern. Thus, the NOAA's physical form (i.e. exposure availability) should be characterised throughout the product lifecycle.

Any material that has come into contact with dispersible engineered NOAAs (that has not been decontaminated) should be considered as belonging to a nanomaterial-bearing waste stream. This includes PPE, wipes, blue roll, blotters and other disposable laboratory materials used during research activities.

Equipment used to manufacture or handle hazardous or potentially hazardous nanomaterials should be decontaminated before it is disposed of correctly (see <u>WMGN17</u> for guidance on electrical items) or reused.

Wastes resulting from decontamination (cleaning solutions, rinse waters etc.) should be treated as nanomaterial-bearing waste, and disposed of as hazardous liquid waste via the University's chemical waste stores.

Waste Nanomaterial	Pre- treatment Prior to Disposal	Containment	Level of Engineering Controls	Method of Disposal	Final Waste Treatment Process (Offsite)
Unbound pure NOAAs (nano-objects, agglomerates and aggregates)	Decant in Fume Hood / Biosafety cabinet with HEPA filters into appropriate sealed bottle	Drip tray	Inside a LEV enclosure or glove box or vented fume cupboard with the hood down	Liquid waste disposal – see <u>EMS 8.1.5</u>	Incineration
Bound NOAAs in Liquid suspensions (including inks)	Decant in Fume Hood / Biosafety cabinet with HEPA filters into appropriate sealed bottle	Drip tray	Inside a LEV enclosure or glove box or vented fume cupboard with the hood down Liquid placed into appropriate sealed Winchester/bottle/drum etc.	Liquid waste disposal – see <u>EMS 8.1.5</u> Soft Solids Chemical only – red bags. See <u>WMGN21</u>	Incineration
Bound NOAAs Solid matrices with NOAAs that are friable	Wet/moisten. Allow to dry naturally in vented fume cupboard or place into plastic tube	Secondary containment before disposal into in sealed zip bag. Where practical this must be done in a vented fume cupboard.	Inside a LEV enclosure or glove box or vented fume hood with HEPA filters with the hood down	Soft Solids Chemical only – red bags. See <u>WMGN21</u> Sharps Infectious & Chemical – Yellow clinical box. See <u>WMGN26</u>	Incineration

Bound NOAAs Solid matrices with NOAAs that are non-friable e.g. silicon wafer substrate / SPE / polymer (non- sharp)	Wet/moisten Allow to dry naturally in fume cupboard	Single containment (if non-sharp) Secondary's continent if sharp before disposal to red bag – examples provided only	General ventilation	Soft Solids Chemical only – red bags. See <u>WMGN21</u>	Incineration
Unbound NOAAs Non-solid matrices e.g. blue towels after cleaning laboratory consumables e.g. silicon substrate / SPE / paper towels / gloves / masks	NA Allow to dry in a vented fume hood / biosafety cabinet with HEPA filters	Secondary containment before disposal into in sealed zip bag where practical. This must be done in a vented fume cupboard or with other suitable form of local exhaust ventilation (LEV)	Inside a LEV enclosure or glove box or vented fume cupboard with the hood down	Soft Solids Chemical only – red bags. See WMGN21 Sharps Infectious & Chemical – Yellow clinical box. See WMGN26	Incineration

Disposal Instructions Disposal Instructions Red bag and liquid NOAA waste Yellow lidded clinical for chemical and infectious contaminated sharps and solids Image: Control of the system of the sys

Swansea University Waste Management Guidance Note WMGN33

Estemal Otemana fem diamagal	Fasternel Otenene for dieneeal
External Storage for disposal	External Storage for disposal
Singleton Campus	Singleton Campus
Grove chemical waste store	Grove chemical waste store
Bay Campus	
Bay chemical waste store - Engineering	Bay Campus
Service Yard	Bay chemical waste store - Engineering Service
	Yard
See EMS 8.1.5 Chemical Waste Store	
User Presedure for dispasal quidence	See WMCN26 Infectious and Chemically
Oser Procedure for disposal guidance	See <u>www.gruzo_miectious_and_Chernically</u>
	Contaminated Solid Waste and Sharps Waste
	(Yellow lidded clinical waste box)
Disposal Cost	

Charge for this service may apply, please contact estates-waste@swansea.ac.uk

For further guidance: please contact <u>Estates-Waste@Swansea.ac.uk</u> and the local University's Biological Safety Officer